

# ASSEMBLY INSTRUCTIONS

## RTS 5M1 LARGE MARSHAL OUTLOOK

### CONGRATULATIONS

Congratulations in choosing a unique product to enhance your slot car track diorama. This can truly be described as a product born from a love for slot cars. Buying this product have made you a member of a very special family, yes you are not dealing with a faceless business, but rather a family of slot car fanatics.

We put hours of skill and more importantly love into our product and it is wonderful to share our love for slot cars with you. May you enjoy the build and have years of joy having it as part of your trackside diorama.

This is a fictitious building, but not unlike the facilities for marshals that you will find at race tracks. We believe that this will enhance your trackside diorama and help to transform it into a realistic scaled reality for you to enjoy.

### WARRANTY

This product is covered by a comprehensive money-back warranty to ensure your absolute satisfaction with your purchase.

### WHO ARE WE?

This product is brought to you by [racetrackscenics.com](http://racetrackscenics.com). If you have not done so already, please visit our website today. You are also most welcome to visit the Facebook pages “**Race Track Scenics Slot Car Scenery**” and “**Johan Malan**” to keep up to date with the latest developments and the launching of exciting new products that may be in the pipeline.

You can contact Kevin Sharpe on  
Email: [racetrackscenics@gmail.com](mailto:racetrackscenics@gmail.com)  
Text in the USA 586 549 2879  
WhatsApp 1-586-549-2879

for any assistance that you might require. Your feedback and a photo or two of your trackside addition will really be appreciated. We love to share in your joy!

## **WHAT IS IN THE KIT?**

In this kit you will find all the laser cut pieces needed to assemble this product. The pieces are still intact in the sheets as they were cut to ensure that all the parts are there. Some of the loose bits inside pieces may have been removed, but they are not part of the finished product. In the section "FAMILIARIZE YOURSELF" below, you will find diagram(s) that identify and explain each piece (component) that you are about to assemble. In the section "PREPARING THE CUT PIECES" below, you will learn how to proceed to prepare the pieces for assembly.

## **WHAT YOU WILL NEED**

We have specifically designed this product so that it is easy to assemble with only a few basic tools. You will need the following:

- a screwdriver
- a sharp hobby knife
- some glue
- a few toothpicks
- a few earbuds can be handy
- a paintbrush or sponge roller and paint or a rattle can or two with spray paint.

There are really two schools of thought as to the right glue to use. Some people prefer a rapid setting glue like most gel super glues, while others prefer a slower setting glue like ordinary cold wood glue. Sometimes more than one part must be assembled almost simultaneously and then a forgiving glue makes life a bit easier. Other times you may want a quick fit and then the rapid setting glue is the obvious choice. Our advice is to see what works best for you, there are no right or wrong, both types will produce a sturdy structure.

You will only need a small amount of glue and remember to look for the surfaces that will be in contact in the end and do not only apply glue to the lugs and sleeves. The latter restrict movement in one plane, but the glue fix it in the perpendicular plane. Using a toothpick is a handy way to apply glue and an earbud can be used to dab away any excess of glue (especially if you use wood glue).


If parts must be at a right angle, you can use any object to assist you in obtaining a square finished product in the end.

## FAMILIARIZE YOURSELF

Have a look at a photo of the finished product (in the later design the flag on the roof was replaced with small billboards).



Now have a look at the next diagram where all the laser cut parts are shown and numbered from **A** to **L**. Next, we will identify which is which and where they fit in.



The structure consists of four walls, the front wall (**B**), the rear wall (**C**) and two side walls (**D**) and (**E**). All the walls fit into the floor (**A**). This is an elevated structure to facilitate better sight for the marshals and therefore there are four columns made up of sides (**K 1-8**) and (**L 1-8**) that fits underneath the floor (**A**) to elevate the structure.

The front balcony is enclosed by three railings (**G**) and (**H 1-2**). They all fit into the floor and the two side railings also fit into the front wall (**B**).

There is a ladder (**J**) that gives access to the back door. The ladder is fixed to the underside of the floor (**A**).

Lastly there is a roof (**F**) that fits over the front and side walls and then rests on the walls.

## **PREPARING THE CUT PIECES**

Firstly, remove all the laser cut parts from the sheets. The sheets can be discarded. Clean the edges of the parts if there are any tiny bits where the parts were fixed to the sheets. This can be done with your knife or even your thumb nail.

We recommend that you start by sanding your finished product with a very light sandpaper to ensure a smooth finish for the end product.

## **WORD OF ADVICE**

We would strongly advise you to do a quick dry assembly before you start gluing the laser cut parts together. Lay out all the parts on your work surface and make sure that the parts are not upside down or mirrored. In most instances it will make no difference, but in others it may be crucial to ensure a perfect product in the end.

Our laser cut parts are specifically cut to very fine tolerances to ensure a snug fit and therefore it is wise to check all fits before gluing parts together. You may need to trim a lug here and there to make assembly easier.

## **PAINTING YOUR PRODUCT**

We would strongly advise you to finish the product with paint or wood stain to make them as appealing as possible. The parts should be primed (2 coats) and painted before final assembly. Spray paint can also be used to get a very smooth finish (the finished product in the photo above has been spray painted). Oil or water-based paint can be used and specialised paints like chalk paint can be used to give unique finishes.

Generally, it is highly advisable to paint/spray before gluing. You may not be able to get to the inside of the structure after it is glued together. Covering all the parts that must not be painted or sprayed with the same colour can be a tedious process. Pre-painting will avoid this process.

Please ensure that no paint clog a slot where a lug must fit in later. The tolerances are often so tight that too thick a layer of paint may cause problems. It is our experiences that a small foam roller instead of a brush, will produce a better finish and far less clogging of sleeves.

Applying a base or undercoat normally makes life easier afterwards. Two coats of primer are advisable because the MDF absorbs a lot of paint. Using a single colour for the undercoat of all parts works quite well from personal experience. You can choose the paint of your preference, whether it is oil or water based. Cleaning brushes and rollers are just so much easier if you use a water base paint. A chalk paste can give a unique finish to walls and give a weathered look if so desired. If you prefer to protect the paint work of your structure you can always apply a clear spray coat.

## **LET'S GET STARTED WITH THE ASSEMBLY**

Place the floor (**A**) upside down on your work surface. The engraving must face downwards. Then start to glue the nubs of the sides of the four columns (**K 1-8**) and (**L 1-8**) into the slots in the floor (**A**). Each column is made up of two wide sides and two narrow sides. All that is needed for a proper sturdy assembly is some glue where any two parts touch each other. The lugs that fit into the slots stop any movement, but the glue holds all the parts together. The sides of the columns must therefore have glue where the sides touch each other (only a little bit of glue is required). Gently press down on the columns to ensure a snug fit. Ensure that all the sides are plumb and square. Carefully turn the sub-assembly around and again press down on the floor to ensure that all the columns touch the ground. Once again assure that all are square and allow the glue to fully set before you proceed.

Next, the nubs of the four walls, the front wall (**B**), the rear wall (**C**) and the two side walls (**D**) and (**E**) can be glued into the slots in the floor (**A**). Proceed to also glue in the nubs of the three railings (**G**) and (**H 1-2**) into the slots in the floor (**A**) and the front wall (**B**). Again, press down gently on the walls and railings to ensure a snug fit. Assure that all pieces are square and plumb and allow the glue to fully set before you proceed.

Turn the sub-assembly around and glue in the ladder (**J**) to fit in underneath the floor (**A**).

Lastly the roof (**F**) can be fitted over the front and side walls. The engraving must face upwards. It is advised to allow the roof to rest on the walls and not to glue it down. This will allow access to the inside of the building at a later stage to add lights or furniture.

## **FINISHING & BRANDING**

We leave the finishing to your imagination and your taste. Do whatever you think will transform this into a structure that will compliment your race track diorama.

## **CONCLUSION**

We sincerely hoped you have enjoyed this assembly and finishing. Please remember to give us some feedback and either send or post some pictures of this product on your track.